Table 1 - Atlas phase 1 trenching Length weighted average channel sample gold / silver results

Trench ID	From Meters	To Meters	Interval ³ meters	Gold g/t	Silver g/t	AuEq ¹ g/t	Gram meter ² AuEq
			Atl	as Gold Zon	е		
TR-AKI-01	47.9	49.1	1.2	2.54	4.53	2.62	3.15
	210.3	216.9	6.6	0.73	4.14	0.81	5.34
		including	4.0	0.95	5.86	1.05	4.21
TR-AKI-02	130.5	132.1	1.6	7.28	5.77	7.38	11.82
	140.1	146.8	6.7	2.33	1.09	2.35	15.78
	158.5	163.1	4.6	1.18	0.46	1.18	5.45
		including_		1.52	0.54	1.53	4.75
	180.4	185.6	5.2	1.46	12.37	1.68	8.75
		including_	1.6	2.63	24.33	3.07	4.91
	also	including_	2.6	1.18	8.27	1.33	3.47
	190.0	198.2	8.2	0.37	3.96	0.44	3.60
		including	2.0	0.51	5.32	0.60	1.21
TR-AKI-03	78.3	79.9	1.6	0.89	0.82	0.90	1.45
	116.8	118.8	2.0	0.01	28.80	0.53	1.06
			Atl	as Silver Zon	e		
TR-AKI-06	20.0	23.5	3.5	0.003	32.29	0.59	2.06
	44.3	46.3	2.0	0.003	45.30	0.83	1.65
	96.6	100.1	3.5	0.003	17.85	0.33	1.14
	109.1	129.3	20.2	0.049	35.91	0.70	14.19
		including	2.0	0.034	40.10	0.76	1.53
	also including _		4.0	0.003	36.35	0.66	2.65
	also including		2.0	0.006	51.60	0.94	1.89
	also including		5.2	0.171	56.74	1.20	6.25
	133.3	160.0	26.7	0.016	54.76	1.01	27.01
	including		4.0	0.003	40.15	0.73	2.93
	also	including	11.2	0.013	92.43	1.69	18.97
	also	including	2.0	0.044	36.40	0.71	1.41
	also	including	1.5	0.033	34.30	0.66	0.98

At a 0.1 g/t AuEq cutoff TR-AKI-06 (104.1-160m) gave 55.9m@0.05g/t Gold and 39.94g/t Silver - 43.14 gram meter

- 1. AuEq (Gold Equivalence) is calculated using the following formula Au + (Ag/55)
- 2. Gram meter AuEq (Gold Equivalence) is calculated using following formula AuEq x interval in meters
- 3. Length weighted average channel Intervals have been calculated at 0.25 g/t AuEq Cut-off & including up to 2m of Internal Dilution at 0.01 g/t
 - 3a. Including intervals composited at 0.5 AuEq55 Cut-off
- 4. Highlighted results are those with a gram meter product larger than 5
- 5. Only gram meter products greater than 1 is shown